

SP-5514 TOUCH POS SYSTEM

ELEGANT, FLEXIBLE AND ECONOMICAL POS SOLUTION



The new Partner Tech SP-5514 POS system combines elegance and flexibility with powerful, energy efficient technology. This grants future-reaching investments. Its seamless, modern design, its technical flexibility and its performance meets every demand. Be it in retail environment, hospitality or for special markets, the SP-5514 fit perfect in all checkouts and store interiors.

From technical point of view, the SP-5514 fulfills all todays requirements such as PCT touch technology (Multi Touch), fanless CPU with high performance, adjustable operator touch monitor, selection of customer displays/monitors and integrated POS peripherals.

All this combinations of the functionalities make the SP-5514 a clever choice for POS solutions of today's changing business environments.

SPECIAL FEATURES

- Bezelfree 14" wide screen TFT LCD with LED back light
- Projected Capacitive Touch (PCT)
- Supports up to 8GB RAM
- Wide range of flexible interfaces, incl. USB 3.0 and Powered USB
- 2nd monitor support
- Spill and dust resistant front panel

OPTIONAL

- Mini PCI-e, e.g. to support WiFi module
- Customer display (2x20 VFD or 7")
- 2nd monitor support (11.6" or 15")
- 3-track MSR, IC card reader
- RFID reader, iButton, Parallel port

SP-5514

MODELL	SP-5514
CPU	Intel® Celeron™ J1900 (2.00GHz up to 2.42GHz), quad core, 2MB L2 Cache, fanless
LCD	Bezelfree 14" TFT-LCD, resolution 1366 x 768, brightness 220cd/m², LED back-light
Touch	Projected Capacitive Touch (Multi Touch) with USB interface
RAM	DDR3L SO-DIMM, 2 slots up to 8GB
Storage	1 x 2.5" SATA HDD or SSD (option)
LAN	1 x RJ-45 10/100/1000 BASE-T Gigabit Ethernet
I/O Interface	2 x COM (DC+0/5/12V: COM 1-2 BIOS selection) 3 x USB 2.0 1 x USB 3.0 1 x RJ-45 Ethernet 1 x RJ-11 Cash drawer control (for 2 cash drawers) 1 x VGA 1 x DC + 12V Out 1 x Mini PCI-e (internal) 1 x Audio connector
Optional Interface Expansion	2 x COM (DC+0/5/12V: COM 3-4 by jumper) or 1 x COM (DC+0/5/12V: COM 3 by jumper) + 1x Parallel port or 3 x Powered USB 12V , 1x Powered USB 24V
Speaker	1 x 3W speaker (internal)
Operating System	Windows 7, POSReady 7, Windows 8.1, Windows 10, Linux (ubuntu)
Power Supply	AC100~240V/DC+12V, 65W / 90W / 180W power adaptor
Dimensions	367mm (W) x 252mm (D) x 297mm (H)
Environment	Operating: Temperature: 0°C ~ +40°C Humidity: 15% ~ 80% Storage: -20°C ~ +60°C 15% ~ 80%
Options	3-track MSR, customer display (2x20 VFD, CD-70), 2nd monitor (PM-116, PM-15BZ PCT) Finger print sensor, LF/HF NFC/RFID reader, SSD, interface expansion boards
Color	black (standard)

*Specification is subject of change without prior notice.

